

ALPHA[®] AUTOCLEAN 40

Aqueous Electronics Cleaner

DESCRIPTION

ALPHA AutoClean 40 is an aqueous flux removal fluid designed for use at full strength. It is available in conveniently sized stacking drums. It has been formulated for efficient removal of pre and post soldering flux residues from flux spray equipment, ovens, pallets, carriers, jigs, and printed circuit assemblies. This water-based product is a carefully researched blend of synergistic surfactants and emulsifiers. These ensure efficient cleaning and inhibition of re-deposition of dissolved soils. It does not rely only upon simple saponification.

READ ENTIRE TECHNICAL DATA SHEET BEFORE USING THIS PRODUCT

FEATURES & BENEFITS

- Highly effective for cleaning flux spray nozzles, ovens, selective soldering pallets, and other equipment
- Does not contain CFC's or chlorinated solvents
- Water-Based
- Excellent efficacy even at ambient temperatures
- Non Acidic
- Efficiently removes high-rosin flux residues
- Environmentally friendly
- Non-Flammable
- Low Cost of Ownership
- Low viscosity
- Rinse with DI water

PRODUCT INFORMATION

| | |
|--------------------------|-------------------------|
| <u>Appearance:</u> | Clear colorless liquid* |
| <u>Flash Point, °F:</u> | None to boiling |
| <u>Specific Gravity:</u> | 1.0 @ 20 °C |
| <u>pH:</u> | < 12 |

- * If stored above 77°F (25°C), the product can become cloudy. Simply shake thoroughly before use.

APPLICATION GUIDELINES

- ALPHA AutoClean 40 should be used as received at 100% concentration.
- Effective at ambient temperatures, performance is optimum at 100 °F (38 °C).
- For batch cleaning, ALPHA AutoClean 40 should be used in a tank designed for aqueous processing.
- ALPHA AutoClean 40 is compatible with most common equipment materials. Not recommended for cleaning aluminum parts.
- High solids rosin based flux materials (such as ALPHA EF-10000) will typically be removed in approximately 3 minutes with agitation* provided by circulation pumps or ultrasonics.
- Rinse cycles can be done with city water with a final rinse cycle in DI water.
- Parts can be dried with hot or circulating air.

* *AutoClean 40 may exhibit foaming when used in some spray cleaning equipment.*

Suggested Process Parameters:

| Process Type | Concentration Range | Temperature Range | Rinse / Dry |
|------------------------|---------------------|---------------------------|-------------|
| Immersion, Agitation | 100% | Ambient to 100 °F (38 °C) | DI / Air |
| Immersion, Soak | 100% | Ambient to 100 °F (38 °C) | DI / Air |
| Immersion, Ultrasonics | 100% | Ambient to 100 °F (38 °C) | DI / Air |
| Manual Wipe | 100% | Ambient to 100 °F (38 °C) | Optional |

The above conditions are meant to be starting ranges. Process parameters may be increased or decreased as needed depending on the specific parts and soils involved. Your Alpha Applications Engineer or Sales Representative can assist you in optimizing your process parameters.

SAFETY & WARNING

It is recommended that the company/operator read and review the Safety Data Sheets for the appropriate health and safety warnings before use. **Safety Data Sheets are available at AlphaAssembly.com**

STORAGE

ALPHA AutoClean 40 has a shelf-life of 1080 days if stored in unopened containers in a cool, dry location between 5 to 30 °C.

CONTACT INFORMATION

**To confirm this document is the most recent version, please contact
Assembly@MacDermidAlpha.com**

www.macdermidalpha.com

| | | |
|--|---|---|
| <p>North America 109 Corporate Blvd. South Plainfield, NJ 07080, USA 800.367.5460</p> | <p>Europe Unit 2, Genesis Business Park Albert Drive Woking, Surrey, GU21 5RW, UK 01483.758400</p> | <p>Asia 8/F., Paul Y. Centre 51 Hung To Road Kwun Tong, Kowloon, Hong Kong 852.3190.3100</p> |
|--|---|---|

Also read carefully warning and safety information on the Safety Data Sheet. This data sheet contains technical information required for safe and economical operation of this product. READ IT THOROUGHLY PRIOR TO PRODUCT USE. Emergency safety directory assistance: US 1 202 464 2554, Europe + 44 1235 239 670, Asia + 65 3158 1074, Brazil 0800 707 7022 and 0800 172 020, Mexico 01800 002 1400 and (55) 5559 1588

DISCLAIMER: All statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. No statement or recommendation shall constitute a representation unless set forth in an agreement signed by officers of seller and manufacturer. NO WARRANTY OF MERCHANTABILITY, WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY IS MADE. The following warranty is made in lieu of such warranties and all other warranties, express, implied, or statutory. Products are warranted to be free from defects in material and workmanship at the time sold. The sole obligation of seller and manufacturer under this warranty shall be to replace any noncompliant product at the time sold. Under no circumstances shall manufacturer or seller be liable for any loss, damage or expense, direct, indirect, incidental or consequential, arising out of the inability to use the product. Notwithstanding the foregoing, if products are supplied in response to a customer request that specifies operating parameters beyond those stated above, or if products are used under conditions exceeding said parameters, the customer by acceptance or use thereof assumes all risk of product failure and of all direct, indirect, incidental and consequential damages that may result from use of the products under such conditions, and agrees to exonerate, indemnify, defend and hold harmless MacDermid, Incorporated and its affiliates therefrom. No suggestion for product use nor anything contained herein shall be construed as a recommendation to use any product in a manner that infringes any patent or other intellectual property rights, and seller and manufacturer assume no responsibility or liability for any such infringement.

© 2019 MacDermid, Inc. and its group of companies. All rights reserved. "(R)" and "TM" are registered trademarks or trademarks of MacDermid, Inc. and its group of companies in the United States and/or other countries.