

# ALPHA NR300-A4K

VOC-Free, No-Clean, No Residue Flux

## DESCRIPTION

**ALPHA NR300-A4K** is an essentially VOC-free<sup>1</sup>, halide-free, rosin/resin free, low solids, no-clean flux. It is formulated for wave soldering of through-hole, mixed technology and surface mount assemblies.

**ALPHA NR300-A4K** provides excellent soldering on bare copper boards with organic coatings. The soldering of bare copper boards is extremely difficult due to the thermal treatments which most boards have previously experienced (reflow and adhesive cure), which generates a strong oxide coating. The flux produces a tack-free surface with high surface insulation resistance and no residue to interfere with electrical testing. **ALPHA NR300-A4K** has a unique formulation that provides high activity with virtually no visible residue with most solder masks.

**ALPHA NR300-A4K** is supplied in a water based vehicle, free of organic solvents and is formulated to help meet the present and future volatile organic compound (VOC) emission regulations. The water vehicle results in a non-flammable product which does not require special storage conditions. A further unique property of the **ALPHA NR300-A4K** formulation is its ability to keep the organic activator system in solution after being submitted to storage temperatures below freezing. **ALPHA NR300-A4K** flux uses a unique blend of organic activators which significantly reduces solder bridging, icicing and solder balling on difficult to solder assemblies.

READ ENTIRE TECHNICAL DATA SHEET BEFORE USING THIS PRODUCT

<sup>1</sup> Trace VOC content, primarily from flux activator volatilization during soldering, measured at 1% as determined per EPA Reference Method 24 using ASTM test procedure D2369. Conventional alcohol-based low solids, no-clean fluxes typically have VOC content in excess of 95%

## FEATURES & BENEFITS

Features	Benefits
VOC-Free	Helps meet air quality regulations
Non-Flammable	Eliminates equipment fires & special storage requirements
High Activity	Excellent soldering, particularly on bare copper boards
No Thinners Required	Reduced operating costs & less frequent solids analysis required
No Visible Residue	Accurate pin testing & enhanced board cosmetics

## APPLICATION GUIDELINES

ALPHA NR300-A4K flux can be applied by spray or wave applications (not intended for foam application). Topside preheat temperatures of 93 to 104 °C (200 to 220 °F) for spray application and of 104 to 116 °C (220 to 240 °F) for wave application are recommended. The optimum preheat settings and conveyor speed required to completely evaporate the water vehicle will be dependent upon the particular wave solder machine being used and the assemblies being processed. Insufficient preheat will be evident by spattering during wave soldering.

ALPHA NR300-A4K flux, unlike conventional fluxes, does not require frequent thinning. Flux solids can be monitored using Alpha's Flux Solids Control Kit #3. If thinning is required, the addition of deionized water is all that is necessary.

For applications which specify cleaning, a plain heated water cleaning step after soldering will remove any slight traces of flux residues.

## PHYSICAL PROPERTIES

Item	Typical Values	Item	Typical Values
Appearance	Clear, colorless liquid	Flash Point (T.C.C.)	None
Solids Content, %wt/wt	4.0	Recommended Thinner	DI Water
Specific Gravity @ 25 °C (77 °F)	1.011 ± 0.002	Shelf Life (from Date of Mfg.)	540 Days
Acid Number (mg KOH/g)	35.4 ± 2.0	IPC J-STD-004 Designation	ORL0
pH	3.2 ± 0.5	Packaging Size	5 Gallons
Halides	None		

## RECYCLING SERVICES

We provide safe and efficient recycling services to help companies meet their environmental and legislative requirements and at the same time, maximize the value of their waste streams.

Our service collects solder dross, solder scrap, and various forms of solder paste waste. Please contact your local sales representative for recycling capabilities in your area or [link here](#).



**SAFETY & WARNING**

It is recommended that the company/operator read and review the Safety Data Sheets for the appropriate health and safety warnings before use. **Safety Data Sheets are available at [MacDermidAlpha.com/assembly-solutions/knowledge-base](http://MacDermidAlpha.com/assembly-solutions/knowledge-base).**

**CONTACT INFORMATION**

To confirm this document is the most recent version, please contact  
**Assembly@MacDermidAlpha.com**  
[www.macdermidalpha.com](http://www.macdermidalpha.com)

<p><b>North America</b>          109 Corporate Blvd.          South Plainfield, NJ 07080, USA          1.800.367.5460</p>	<p><b>Europe</b>          Unit 2, Genesis Business Park          Albert Drive          Woking, Surrey, GU21 5RW, UK          44.01483.758400</p>	<p><b>Asia</b>          8/F., Paul Y. Centre          51 Hung To Road          Kwun Tong, Kowloon, Hong Kong          852.3190.3100</p>
---	--	---

Also read carefully warning and safety information on the Safety Data Sheet. This data sheet contains technical information required for safe and economical operation of this product. READ IT THOROUGHLY PRIOR TO PRODUCT USE . Emergency safety directory assistance: US 1 202 464 2554, Europe + 44 1235 239 670, Asia + 65 3158 1074, Brazil 0800 707 7022 and 0800 172 020, Mexico 01800 002 1400 and (55) 5559 1588

DISCLAIMER: All statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. No statement or recommendation shall constitute a representation unless set forth in an agreement signed by officers of seller and manufacturer. NO WARRANTY OF MERCHANTABILITY, WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY IS MADE. The following warranty is made in lieu of such warranties and all other warranties, express, implied, or statutory. Products are warranted to be free from defects in material and workmanship at the time sold. The sole obligation of seller and manufacturer under this warranty shall be to replace any noncompliant product at the time sold. Under no circumstances shall manufacturer or seller be liable for any loss, damage or expense, direct, indirect, incidental or consequential, arising out of the inability to use the product. Notwithstanding the foregoing, if products are supplied in response to a customer request that specifies operating parameters beyond those stated above, or if products are used under conditions exceeding said parameters, the customer by acceptance or use thereof assumes all risk of product failure and of all direct, indirect, incidental and consequential damages that may result from use of the products under such conditions, and agrees to exonerate, indemnify, defend and hold harmless MacDermid, Incorporated and its affiliates therefrom. No suggestion for product use nor anything contained herein shall be construed as a recommendation to use any product in a manner that infringes any patent or other intellectual property rights, and seller and manufacturer assume no responsibility or liability for any such infringement.

© 2019 MacDermid, Inc. and its group of companies. All rights reserved. "(R)" and "TM" are registered trademarks or trademarks of MacDermid, Inc. and its group of companies in the United States and/or other countries.