

## ALPHA<sup>®</sup> PV-50

### No-Clean Tabbing And Stringing Flux

#### DESCRIPTION

**ALPHA PV-50** Tabbing and Stringing flux is our lowest solids, alcohol based, zero-halogen, halide and rosin free formulation designed to provide the attributes of excellent solderability in module assembly processes where low temperature or no pre-heating is followed by a soldering step using standard heating methods. Delivers high reliability in both Pb-free and SnPb applications. Additionally, it provides outstanding solder joint cosmetics with a uniform, tack free residue and low equipment maintenance.

READ ENTIRE TECHNICAL DATA SHEET BEFORE USING THIS PRODUCT

#### FEATURES & BENEFITS

- Very low solids produces high electrical reliability, low, tack-free, residues and minimal assembly equipment maintenance and cleaning
- Fast wetting
- Defect-free soldering
- Accurate in circuit testing
- Can be applied by spray or other application method

#### APPLICATION GUIDELINES

ALPHA PV-50 flux is engineered for most standard solar module assembly applications. Perfect for processes using no pre-heat or low temperature pre-heating along with standard temperature reflow, no special cooling or pre-bake required. Care should be taken to ensure flux is applied only to those areas being soldered and to avoid overspray or other excessive loading. Like all no-clean fluxes, no post process cleaning is needed.

ALPHA PV-50 flux can be maintained by titration. Assistance in controlling the flux by this method can be obtained through our technical department.

**TECHNICAL DATA**

Physical Properties	Typical Values	Parameters/Test Method	Typical Values
Appearance	Colorless to light yellow liquid	pH, 5% v/v aqueous solution	2.8 to 4.2
Solids Content, wt/wt	1.36%	Recommended Thinner	ALPHA 425
Specific Gravity @ 25 °C (77 °C)	0.798 to 0.804	Shelf Life	12 months
Acid Number (mg KOH/g)	10.7 ± 1.1	IPC J-STD-004 Designation	ORL0
Flash Point (T.C.C.)	13 °C		

**CORROSION & ELECTRICAL TESTING**
**Corrosion Testing**

Test	Requirement for ORL0	Results
Silver Chromate Paper IPC-TM 650 Test Method 2.3.33	No detection of halide	Pass
Copper Mirror Tests IPC-TM 650 Test Method 2.6.15	No complete removal of copper	Pass
Copper Corrosion Test IPC-TM 650 Test Method 2..3.32	No evidence of corrosion	Pass

**J-STD-004B TM 2.6.3.7 Surface Insulation Resistance**

Test	Requirements	Lowest Recorded Reading <sup>1</sup>	Day 7 Results <sup>2</sup>
"Comb-Down" Un-cleaned	1.0 x 10 <sup>8</sup> Ω minimum	2.5 x 10 <sup>8</sup> Ω	2.2 x 10 <sup>9</sup> Ω
"Comb-Up" Un-cleaned	1.0 x 10 <sup>8</sup> Ω minimum	1.9 x 10 <sup>9</sup> Ω	5.0 x 10 <sup>10</sup> Ω
Control Boards	2.0 x 10 <sup>8</sup> Ω minimum	7.9 x 10 <sup>8</sup> Ω	1.0 x 10 <sup>11</sup> Ω

IPC Test Condition (per J-STD-004B / IPC-TM-650 Test Method 2.6.3.7): 40 °C/90% RH, 12.5V bias, measurements taken every 20 minutes for 7 days, IPC B-24 board (0.4 mm lines, 0.5 mm spacing).

<sup>1</sup> – This is the lowest reading observed out of 4545 total readings recorded

<sup>2</sup> – This is the geometric mean of the 9 final readings recorded for the 3 coupons tested.

**RECYCLING SERVICES**

We provide safe and efficient recycling services to help companies meet their environmental and legislative requirements and at the same time, maximize the value of their waste streams.

Our service collects solder dross, solder scrap, and various forms of solder paste waste. Please contact your local sales representative for recycling capabilities in your area or [link here](#).



**SAFETY & WARNING**

It is recommended that the company/operator read and review the Safety Data Sheets for the appropriate health and safety warnings before use. **Safety Data Sheets are available at [MacdermidAlpha.com/assembly-solutions/knowledge-base](http://MacdermidAlpha.com/assembly-solutions/knowledge-base).**

**CONTACT INFORMATION**

**To confirm this document is the most recent version, please contact [Assembly@MacDermidAlpha.com](mailto:Assembly@MacDermidAlpha.com)**

[www.macdermidalpha.com](http://www.macdermidalpha.com)

<p><b>North America</b> 109 Corporate Blvd. South Plainfield, NJ 07080, USA 1.800.367.5460</p>	<p><b>Europe</b> Unit 2, Genesis Business Park Albert Drive Woking, Surrey, GU21 5RW, UK 44.01483.758400</p>	<p><b>Asia</b> 8/F., Paul Y. Centre 51 Hung To Road Kwun Tong, Kowloon, Hong Kong 852.3190.3100</p>
--	--	---

Also read carefully warning and safety information on the Safety Data Sheet. This data sheet contains technical information required for safe and economical operation of this product. READ IT THOROUGHLY PRIOR TO PRODUCT USE . Emergency safety directory assistance: US 1 202 464 2554, Europe + 44 1235 239 670, Asia + 65 3158 1074, Brazil 0800 707 7022 and 0800 172 020, Mexico 01800 002 1400 and (55) 5559 1588

DISCLAIMER: All statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. No statement or recommendation shall constitute a representation unless set forth in an agreement signed by officers of seller and manufacturer. NO WARRANTY OF MERCHANTABILITY, WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY IS MADE. The following warranty is made in lieu of such warranties and all other warranties, express, implied, or statutory. Products are warranted to be free from defects in material and workmanship at the time sold. The sole obligation of seller and manufacturer under this warranty shall be to replace any noncompliant product at the time sold. Under no circumstances shall manufacturer or seller be liable for any loss, damage or expense, direct, indirect, incidental or consequential, arising out of the inability to use the product. Notwithstanding the foregoing, if products are supplied in response to a customer request that specifies operating parameters beyond those stated above, or if products are used under conditions exceeding said parameters, the customer by acceptance or use thereof assumes all risk of product failure and of all direct, indirect, incidental and consequential damages that may result from use of the products under such conditions, and agrees to exonerate, indemnify, defend and hold harmless MacDermid, Incorporated and its affiliates therefrom. No suggestion for product use nor anything contained herein shall be construed as a recommendation to use any product in a manner that infringes any patent or other intellectual property rights, and seller and manufacturer assume no responsibility or liability for any such infringement.

© 2019 MacDermid, Inc. and its group of companies. All rights reserved. "(R)" and "TM" are registered trademarks or trademarks of MacDermid, Inc. and its group of companies in the United States and/or other countries.