

ACT5050

Acrylic Thinners

DESCRIPTION

ACT5050 is a high purity solvent blend designed for use with Electrolube Acrylic Protective Lacquer **APL5050**.

The primary use of **ACT5050** is to dilute **APL5050** for use in dip coating applications. This product has been formulated for professional use only.

READ ENTIRE TECHNICAL BULLETIN BEFORE USING THIS PRODUCT

APPROVALS

Standard	Status
RoHS Compliant (2015/863/EU)	Yes

PRODUCT INFORMATION

For available packaging sizes please visit:

electrolube.com

PHYSICAL PROPERTIES

Category	Results	
Liquid Properties		
Appearance	Clear, Colorless Liquid	
Density @ 20 °C (g/mL)	0.85	
VOC Content	100 %	
Flash Point (°C)	< 0	



TYPICAL PRODUCT APPLICATION

Dip Coating

ACT5050 may be used to maintain the viscosity of conformal coatings in open tanks used in dip coating processes. Over time, the solvent within the coatings evaporates. This increases the viscosity and produces a thicker coating. This solvent loss must be replaced to maintain the correct viscosity and provide an economical coating thickness.

The amount of ACT5050 to be added depends on the total volume of the tank, ambient temperature and rate of use. ACT5050 should be added slowly, allowing the viscosity of the coating to alter prior to adding additional thinners.

ACT5050 is a flammable solvent blend and should be used in a well-ventilated area. All sources of ignition must be avoided. Please refer to the separate Health & Safety Data Sheet for further details.

ADDITIONAL INFORMATION

Shelf Life: 72 Months



ELECTROLUBE

SAFETY & WARNING

It is recommended that the company/operator read and review the Safety Data Sheets for the appropriate health and safety warnings before use. **Safety Data Sheets are available.**

CONTACT INFORMATION

To confirm this document is the most recent version, please contact TechnicalSupportTeam@hkw.co.uk

www.electrolube.com

North America 109 Corporate Blvd. South Plainfield, NJ 07080, USA 1.800.367.5460	Europe Ashby Park Coalfield Way Ashby de la Zouch Leicestershire, LE65 1JR, UK 44 01530 41960	Asia 8/F., Paul Y. Centre 51 Hung To Road Kwun Tong, Kowloon, Hong Kong 852.3190.3100
	44.01530.41960	

Also read carefully warning and safety information on the Safety Data Sheet. This data sheet contains technical information required for safe and economical operation of this product. READ IT THOROUGHLY PRIOR TO PRODUCT USE . Emergency safety directory assistance: US 1 202 464 2554, Europe + 44 1235 239 670, Asia + 65 3158 1074, Brazil 0800 707 7022 and 0800 172 020, Mexico 01800 002 1400 and (55) 5559 1588

DISCLAIMER: All statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. No statement or recommendation shall constitute a representation unless set forth in an agreement signed by officers of seller and manufacturer. NO WARRANTY OF MERCHANTABILITY, WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY IS MADE. The following warranty is made in lieu of such warranties and all other warranties, express, implied, or statutory. Products are warranted to be free from defects in material and workmanship at the time sold. The sole obligation of seller and manufacturer under this warranty shall be to replace any noncompliant product at the time sold. Under no circumstances shall manufacturer or seller be liable for any loss, damage or expense, direct, indirect, incidental or consequential, arising out of the inability to use the product. Notwithstanding the foregoing, if products are used bave, or if products are used under conditions exceeding said parameters, the customer by acceptance or use thereof assumes all risk of product fallure and of all direct, incidental and consequential damages that may result from use of the product use nor anything contained herein shall be construed as a recommendation to use any product in a manufacture and reprotections exceeding soft and its affiliates therefrom. No suggestion for product use nor anything contained herein shall be construed as a recommendation to use any product in a manufacturer and parted to rother intellectual property rights, and seller and manufacturer and responsibility of iability for any such infringement.

© 2019 MacDermid, Inc. and its group of companies. All rights reserved. "(R)" and "TM" are registered trademarks or trademarks of MacDermid, Inc. and its group of companies in the United States and/or other countries.

