TECHNICAL DATA SHEET



ALPHA® TRUEHEIGHT® SPACER

Tape & Reel Packaging / Spacer with Solderable Surface

DESCRIPTION

ALPHA TrueHeight Spacers are burr-free, non-collapse copper discs coated with a barrier layer of nickel and finish coated with flash gold. **ALPHA TrueHeight Spacers** are designed to be automatically placed and reflowed onto a printed circuit board pad printed with a nominal amount of solder paste. Since all sides of the spacer are coated, reflow does not result in exposed copper.

After reflow, the **ALPHA TrueHeight Spacer** provides a precise standoff height. Electronic components that are reflow soldered can benefit from the use of **ALPHA TrueHeight Spacers** to improve soldering results, such as to prevent corner signal shorting on large BGA devices with characteristic warping. Through hole components that need to be reflow soldered but do not contain sufficient standoff height can benefit from the use of **ALPHA TrueHeight Spacers**.

READ ENTIRE TECHNICAL DATA SHEET BEFORE USING THIS PRODUCT

FEATURES & BENEFITS

Features

- Non-collapse spacer function
- Nickel/ gold coated copper disc
- Burr free construction
- Excellent height dimensional tolerance as low as ± 0.010mm
- Fast placement utilizing standard pick and place equipment
- 7 inch standard IEC reels available

Benefits

- Burr free construction ensures repeatable height after reflow
- Nickel/ gold plating ensures no exposed copper after reflow
- Gold coating ensures highly solderable surface
- Tape and reel packaging for easy integration into standard assembly processes
- Excellent pick and place performance








PRODUCT INFORMATION

Part Dimensions



Size	а		b	
	mm	inch	mm	inch
DS-D076H010	0.76	0.030	0.10	0.004
DS-D076H025	0.76	0.030	0.25	0.010
DS-D076H030	0.76	0.030	0.30	0.012
DS-D076H038	0.76	0.030	0.38	0.015
DS-D050H025	0.50	0.020	0.250	0.010
DS-D050H030	0.50	0.020	0.300	0.012

Tolerance on the part dimension 'a': ±0.05mm

Tolerances on the part dimensions 'b': 0.10 ±0.010mm; 0.25 ±0.013mm; 0.30 ±0.015mm; 0.38 ±0.020mm

Contact your local sales representative for the orderable item number for this part type.

APPLICATION GUIDELINES

ALPHA TrueHeight Spacers are used to maintain a fixed height off the printed circuit board for electronic components. For components such as Ball Grid Array packages, excessive warping during reflow soldering can result in the corner signals shorting against each other as the "frowning" component corners come in near direct contact with the PCB. By adding spacers on the corners of the device, a minimum height is maintained, thus preventing signal shorting.

In applications such as reflow soldering of through hole components, adequate clearance between component body and PCB must be maintained to ensure clearance for solder paste print or preforms placed into the paste to add solder volume. If a though hole component does not have adequate clearance off the PCB, ALPHA TrueHeight Spacers can be added to the PCB to enable reflow soldering. This will reduce processing costs (eliminate wave soldering) and improve performance (increase hole fill).



Issue: 03 September 2024




TECHNICAL DATA SHEET

TECHNICAL DATA

Alloy Information

All ALPHA TrueHeight Spacers are constructed of copper with nickel/gold finish.

Tape and Reel Packaging Information



	Tape Dimensions			
Part Type mm	W	P0	P1	
	mm	mm	mm	
All sizes	8	4	2	

Issue: 03 September 2024



TECHNICAL DATA SHEET

RECYCLING SERVICES

We provide safe and efficient recycling services to help companies meet their environmental and legislative requirements and at the same time, maximize the value of their waste streams.

Our service collects solder dross, solder scrap, and various forms of solder paste waste. Please contact your local sales representative for recycling capabilities in your area.



SAFETY & WARNING

It is recommended that the company/operator read and review the Safety Data Sheets for the appropriate health and safety warnings before use. **Safety Data Sheets are available.**

STORAGE

The parts are packaged in ESD safe reels.

CONTACT INFORMATION

www.macdermidalpha.com

North America
140 Centennial Avenue
Piscataway, NJ 08854
1.800.367.5460

EuropeUnit 2, Genesis Business Park
Albert Drive
Woking, Surrey, GU21 5RW, UK
44.01483.758400

Asia 14 Joo Koon Cresce

14 Joo Koon Crescent, Singapore 629014 65.6430.0700

Also read carefully warning and safety information on the Safety Data Sheet. This data sheet contains technical information required for safe and economical operation of this product. READ IT THOROUGHLY PRIOR TO PRODUCT USE . Emergency safety directory assistance: US 1 202 464 2554, Europe + 44 1235 239 670, Asia + 65 3158 1074, Brazil 0800 707 7022 and 0800 172 020, Mexico 01800 002 1400 and (55) 5559 1588

DISCLAIMER: All statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. No statement or recommendation shall constitute a representation unless set forth in an agreement signed by officers of seller and manufacturer. NO WARRANTY OF MERCHANTABILITY, WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY IS MADE. The following warranty is made in lieu of such warranties and all other warranties, express, implied, or statutory. Products are warranted to be free from defects in material and workmanship at the time sold. The sole obligation of seller and manufacturer under this warranty shall be to replace any noncompliant product at the time sold. Under no circumstances shall manufacturer or seller be liable for any loss, damage or expense, direct, indicental or consequential, arising out of the inability to use the product. Notwithstanding the foregoing, if products are supplied in response to a customer request that specifies operating parameters beyond those stated above, or if products are used under conditions exceeding said parameters, the customer by acceptance or use thereof assumes all risk of product failure and of all direct, indirect, incidental and consequential damages that may result from use of the products under such conditions, and agrees to exonerate, indemnify, defend and hold harmless MacDermid, Incorporated and its affiliates therefrom. No suggestion for product use nor anything contained herein shall be construed as a recommendation to use any product in a manner that infringes any patent or other intellectual property rights, and seller and manufacturer assume no responsibility or liability for any such infringement.

© 2019 MacDermid, Inc. and its group of companies. All rights reserved. "(R)" and "TM" are registered trademarks or trademarks of MacDermid, Inc. and its group of companies in the United States and/or other countries.

